

# Osprzęt i wyposażenie

R-M-PA


metr., PG




|                           |                                                  |
|---------------------------|--------------------------------------------------|
| Material                  | poliamid (typ A/ typ B),<br>polipropylen (typ C) |
| Temperatura ciągłej pracy | -20 °C – 80 °C                                   |
| Kolory                    | czarny (RAL9005)                                 |




typ A



typ B



typ C



| AG         | IG         | typ | GL<br>mm | H<br>mm | d<br>mm | mm | nr zamów.     |
|------------|------------|-----|----------|---------|---------|----|---------------|
| M 16 x 1,5 | M 12 x 1,5 | B   | 8        | 6       | 10      | 20 | 1.273.1612.50 |
| M 20 x 1,5 | M 16 x 1,5 | B   | 8        | 6       | 13,5    | 25 | 1.273.2016.50 |
| M 25 x 1,5 | M 20 x 1,5 | B   | 8        | 6       | 18      | 29 | 1.273.2520.50 |
| M 32 x 1,5 | M 25 x 1,5 | B   | 10       | 6       | 23      | 36 | 1.273.3225.50 |
| M 40 x 1,5 | M 32 x 1,5 | C   | 15       | 5       | 30      |    | 1.273.4032.50 |
| M 50 x 1,5 | M 40 x 1,5 | C   | 15       | 5       | 38      |    | 1.273.5040.50 |
| M 63 x 1,5 | M 50 x 1,5 | C   | 15       | 5       | 48      |    | 1.273.6350.50 |
| M 25 x 1,5 | PG 13,5    | B   | 8        | 6       | 18      | 29 | 1.273.2513.50 |
| M 25 x 1,5 | PG 16      | A   | 8        | 14      | 18      | 29 | 1.273.2516.50 |
| M 32 x 1,5 | PG 21      | A   | 10       | 15      | 25      | 36 | 1.273.3221.50 |
| M 40 x 1,5 | PG 29      | A   | 10       | 15      | 33      | 45 | 1.273.4029.50 |
| M 50 x 1,5 | PG 36      | A   | 12       | 17      | 43      | 55 | 1.273.5036.50 |
| M 63 x 1,5 | PG 42      | C   | 15       | 5       | 52      |    | 1.273.6342.50 |
| PG 9       | M 12 x 1,5 | C   | 15       | 19      | 8,5     |    | 1.273.0912.11 |
| PG 11      | M 16 x 1,5 | C   | 15       | 19      | 11,5    |    | 1.273.1116.11 |
| PG 13,5    | M 16 x 1,5 | B   | 8        | 6       | 14      | 25 | 1.273.1316.11 |
| PG 16      | M 20 x 1,5 | A   | 8        | 13      | 16      | 27 | 1.273.1620.11 |
| PG 21      | M 25 x 1,5 | C   | 15       | 19      | 20,5    |    | 1.273.2125.11 |
| PG 29      | M 32 x 1,5 | C   | 15       | 19      | 28      |    | 1.273.2932.11 |
| PG 36      | M 40 x 1,5 | C   | 15       | 5       | 38      |    | 1.273.3640.11 |
| PG 42      | M 40 x 1,5 | C   | 15       | 5       | 38      |    | 1.273.4240.11 |
| PG 48      | M 50 x 1,5 | C   | 15       | 5       | 38      |    | 1.273.4850.11 |